



BV LCIE
CHINA
Number

N°1766AS11SXP26545

ATTESTATION of conformity with European Directives



Product: PV inverter (Grid-tied photovoltaic inverter)
Reference: X3-4.0-S-D, X3-4.0-S-N, X3-4.0-T-D, X3-4.0-T-N, X3-5.0-S-D, X3-5.0-S-N, X3-5.0-T-D, X3-5.0-T-N, X3-6.0-T-D, X3-6.0-T-N, X3-7.0-T-D, X3-7.0-T-N, X3-8.0-T-D, X3-8.0-T-N, X3-9.0-T-D, X3-9.0-T-N, X3-10.0-T-D, X3-10.0-T-N
Issued to: SolaX Power Network Technology (Zhe jiang) Co. , Ltd.
Address: No. 288 Shizhu Road, Tonglu Economic Development Zone, Dongxing District 311500, Tonglu City, Zhejiang Province, People's Republic of China
Manufacturer: SolaX Power Network Technology (Zhe jiang) Co. , Ltd.
Technical characteristics: See next page

The submitted sample of the above equipment has been tested for  marking according to following European Directive and following standards:

Low Voltage Directive 2014/35/EU

Standards	Report number	Report date
EN 62109-1:2010	SXP-17MY0742FTSP-1	29/11/2017
EN 62109-2:2011	SXP-17MY0742FTSP-2	29/11/2017

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product
The  marking may be affixed if all relevant and effective European Directives with  are applicable

Shanghai (P.R. China),), Nov 29th, 2017.



Dio Zhang
Operation Manager



This document shall not be reproduced, except in full, without the written approval of BV LCIE China.
Information given in this document, are related to the tested specimen of the described electrical sample.

LCIE CHINA
必维欧亚电气技术咨询服务(上海)有限公司
Version 3/2016.02.19

Building 4, No. 518, Xin Zhuan Road,
CaoHejing Songjiang High-Tech Park,
Shanghai P.R.C (201612)

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com

Model / Type	X3-4.0-S-D, X3-4.0-S-N	X3-4.0-T-D, X3-4.0-T-N	X3-5.0-S-D, X3-5.0-S-N
Operating voltage range [V]	160-950	160-780	160-950
Rated Input DC voltage [V]	600	600	600
Max Input DC current [A]	11	11/11	11
Output AC voltage [V]	230Vac, 50/60Hz	230Vac, 50/60Hz	230Vac, 50/60Hz
Max.Output AC current [A]	3*6,4	3*6,4	3*8,0
Output power [VA]	4000	4000	5000
Model / Type	X3-5.0-T-D, X3-5.0-T-N	X3-6.0-T-D, X3-6.0-T-N	X3-7.0-T-D, X3-7.0-T-N
Operating voltage range [V]	160-780	160-780	160-950
Rated Input DC voltage [V]	600	600	600
Max Input DC current [A]	11/11	11/11	11/11
Output AC voltage [V]	230Vac, 50/60Hz	230Vac, 50/60Hz	230Vac, 50/60Hz
Max.Output AC current [A]	3*8,0	3*9,6	3*11,2
Output power [VA]	5000	6000	7000
Model / Type	X3-8.0-T-D, X3-8.0-T-N	X3-9.0-T-D, X3-9.0-T-N	X3-10.0-T-D, X3-10.0-T-N
Operating voltage range [V]	160-950	160-950	160-950
Rated Input DC voltage [V]	600	600	600
Max Input DC current [A]	11/11	11/11	11/11
Output AC voltage [V]	230Vac, 50/60Hz	230Vac, 50/60Hz	230Vac, 50/60Hz
Max.Output AC current [A]	3*12,8	3*14,4	3*16,0
Output power [VA]	8000	9000	10000

Shanghai (P.R. China),), Nov 29th, 2017.



Dio Zhang
Operation Manager



This document shall not be reproduced, except in full, without the written approval of BV LCIE China.
Information given in this document, are related to the tested specimen of the described electrical sample.

LCIE CHINA
必维欧亚电气技术咨询服务(上海)有限公司

Building 4, No. 518, Xin Zhuan Road,
CaoHejing Songjiang High-Tech Park,
Shanghai P.R.C (201612)

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com

Version 3/2016.02.19