



A P P R O V A L S ®

# Certificate of Suitability

## \* Addendum \*

**Certificate No.:** SAA193109

**Date of Issue:** 11 November 2019

**Class Description:** NP: Non-Prescribed

**Product Description:** PV Inverter (Grid-tied Photovoltaic Inverter)

Additional Models	Trade Name	Rating
X1-1.5-S-D(L)	SOLAXPOWER	Input: MPP Voltage range: 55-380Vdc, Max 400Vdc, Max 10A, Isc: 12A Output: 220/230/240V~ 50/60Hz Max 7.5A, 1500VA
X1-1.5-S-N(L)	SOLAXPOWER	Input: MPP Voltage range: 55-380Vdc, Max 400Vdc, Max 10A, Isc: 12A Output: 220/230/240V~ 50/60Hz Max 7.5A, 1500VA
X1-1.5-S-D(O)	SOLAXPOWER	Input: MPP Voltage range: 55-380Vdc, Max 400Vdc, Max 10A, Isc: 12A Output: 220/230/240V~ 50/60Hz Max 7.5A, 1500VA
X1-1.5-S-N(O)	SOLAXPOWER	Input: MPP Voltage range: 55-380Vdc, Max 400Vdc, Max 10A, Isc: 12A Output: 220/230/240V~ 50/60Hz Max 7.5A, 1500VA
X1-2.0-S-N(L)	SOLAXPOWER	Input: MPP Voltage range: 55-380Vdc, Max 400Vdc, Max 10A, Isc: 12A Output: 220/230/240V~ 50/60Hz Max 9.5A, 2000VA
X1-2.0-S-D(O)	SOLAXPOWER	Input: MPP Voltage range: 55-380Vdc, Max 400Vdc, Max 10A, Isc: 12A Output: 220/230/240V~ 50/60Hz Max 9.5A, 2000VA
X1-2.0-S-N(O)	SOLAXPOWER	Input: MPP Voltage range: 55-380Vdc, Max 400Vdc, Max 10A, Isc: 12A Output: 220/230/240V~ 50/60Hz Max 9.5A, 2000VA

For and on Behalf of  
SAA Approvals Pty Ltd


SAA Approvals Pty Ltd as accredited by JAS-ANZ under ISO/IEC 17065 and declared a RECS under *Qld Electrical Safety Act 2002 and Electrical Safety Regulations 2013* certifies in accordance with the SAA Approvals Electrical Product Safety Certification Scheme that the product nominated in this certificate complies with standard/s listed.

When using the RCM the requirements of all relevant parts of AS/NZS 4417 applicable to the article must be fulfilled.

For SAA Contact Details and to verify this Certificate go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



Issued: 11-11-19 193109/3